



EXPERIENCE

THE NEXT GENERATION OF FARMING POWER



KEY FEATURES

- >> No SCR and DPF
- Engine Mounted ECU
- >> Roller tappet arrangement
- Hydraulic Latch Adjuster (HLA) arrangement eliminates the need for manual tappet adjustment
- Four valves per cylinder configuration

- MITA Hydraulics with 4 Spool valves
- >> Central Direct Injection
- >> Copper Radiator for effective engine cooling
- >> 3200Kg Lifting Capacity

Technical Specification



W ENGINE

Type: Kirloskar 4R 1190, 74.5 HP, 2200 RPM, 4 Cylinder, Naturally Aspirated, CRDI.

Bore x stroke: 110mm x 125mm

Cubic Capacity: 4760 cc

Air Filter: Dry Type Filter with Choke Sensor

Cooling: Copper Radiator with Coolant - Cooled System

& Overflow Reservoir

III TRANSMISSION

Clutch: Independent

Gear Box: Carraro Synchro Shuttle Transmission

12 Forward + 12 Reverse / 24 Forward + 24 Reverse

 Normal
 Creeper
 Advanced

 Speeds:
 12F+12R
 12F+12R
 24F + 24R

III POWER TAKE OFF

Type: 540,540E, GPTO, 6 Splines

W HYDRAULICS

Hydraulics Type: MITA Hydraulics with 4 Spool valves

2500Kg capacity - Without External Cylinder

Lifting Capacity: 2800Kg capacity - With 1 external hydraulic cylinder

3200Kg With 2 external hydraulic cylinders

3 Point linkage: Category-II Automatic Depth & Draft Control (ADDC)

W STEERING

Type: Adjustable steering

W DIMENSIONS AND WEIGHT

	2WD	4WD	
Total Weight: (Incl. Accessories)	3010 Kg	3460 Kg	
Wheel Base:	2400 mm	2400 mm	
Overall Length:	4230 mm	4230 mm	
Overall Width:	1997 mm	1997 mm	
Track Width:	1550 mm	1550 mm	
Ground Clearance:	425 mm	425 mm	

**** WHEELS AND TYRES

	שווד		2110	
	Standard	Optional	Standard	Optional
Front:	12.4x24	11.2x24	9.0x16	7.5x16
Rear:	18.4x30	16.9x30	18.4x30	16.9x30

VV FUEL TANK

Capacity 85L

XX ELECTRICAL SYSTEM

Battery 180Ah, 12V Alternator 90 Amp. Starter Motor 2.7 kW, 12V

W KEY HIGHLIGHTS

500 Hours Service Interval • Battery cut off switch • Spacious Platform Heat Guard • Water Separator • ROPS & Canopy (Optional)

Powerful, Technologically Advanced KIRLOSKAR 4R 1190 CRDI ENGINE


- 2200 RPM for Maximum Efficiency
- Optimized Fuel Efficiency with Advanced Injection System





Carraro Transmission

The Carraro Synchro Shuttle Transmission 12F+12R and 24F+24R, ensure smooth shifting, precision control, and efficient power delivery across all terrains.



Roller Tappet Arrangement

Reduces friction and wear, enhancing engine efficiency and ensuring smoother valve operation for longer engine life and better fuel economy.



HLA Arrangement For Rocker Lever

Hydraulic Latch Adjusters (HLA) ensure precise valve clearance, reducing maintenance requirements and enhancing engine longevity with automatic adjustments.

KARTAR TRACTORS PRIVATE LIMITED

Shop No.22, Grain Market, Bhadson, Patiala. Punjab, 147202

For more information, Please contact our Authorized Dealer or call our Customer Care.

KARTAR GENUINE PARTS

Economical | Reliable | Easily Available



E-Brochure